

**IN THE CLAIMS**

Please cancel claims 5, 11, 15, 16 and 19 without prejudice or disclaimer, amend claims 1, 6 thru 10, 12, 13, 17 and 20, and add claims 21 thru 25, as follows:

1           1. (Currently Amended) An apparatus, comprising:

2           a tension mask having a screen part for transmitting electron beams, the screen part  
3           having a first area including a center region of the screen part, and having a second area  
4           distinguishable from the first area and not including the center region of the screen part; and  
5           a mask frame coupled to said tension mask for reinforcing structural strength of said  
6           tension mask while applying tension to said tension mask;

7           the screen part including a plurality of real slots, dummy slots and strip parts, the real  
8           slots being located in the first area, the dummy slots being located in the second area;

9           the screen part having a first edge region substantially parallel to an X axis, the first  
10          area being symmetrically formed around a first imaginary line parallel to the X axis, the first  
11          area being symmetrically formed around a second imaginary line perpendicular to the X axis;  
12          the first area being concavely shaped in a middle region of the second imaginary line.

1           2. (Original) The apparatus of claim 1, the real slots in the first area being formed by  
2           a plurality of real bridges in the first area, each real bridge connecting adjacent ones of the  
3           strip parts to each other, the dummy slots in the second area being formed by a plurality of  
4           dummy bridges in the second area.

1           3. (Original) The apparatus of claim 2, the first area being symmetrically formed  
2 around a first axis and being symmetrically formed around a second axis perpendicular to the  
3 first axis.

1           4. (Original) The apparatus of claim 3, the first and second axes passing through a  
2 center point at a center of the screen part.

Claim 5. (Canceled)

1           6. (Currently Amended) The apparatus of claim [[5]] 1, the first and second  
2 imaginary lines being straight lines passing through a center point at a center of the screen  
3 part.

1           7. (Currently Amended) [[The]] An apparatus of claim 6, comprising:  
2 a tension mask having a screen part for transmitting electron beams, the screen part  
3 having a first area including a center region of the screen part, and having a second area  
4 distinguishable from the first area and not including the center region of the screen part; and  
5 a mask frame coupled to said tension mask for reinforcing structural strength of said  
6 tension mask while applying tension to said tension mask;  
7 the screen part including a plurality of real slots, dummy slots and strip parts, the real

8 slots being located in the first area, the dummy slots being located in the second area;

9 the screen part having a first edge region substantially parallel to an X axis, the first  
10 area being symmetrically formed around a first imaginary line parallel to the X axis, the first  
11 area being symmetrically formed around a second imaginary line perpendicular to the X axis;

12 the screen part having the first edge region on the X axis and a second edge region on  
13 a Y axis perpendicular to the X axis, the X and Y axes crossing each other at a corner region  
14 of the screen part, the first edge region having a length  $x'$  and the second edge region having  
15 a length  $y'$ , the first area being bordered by six lines connecting six points  $P_1$  to  $P_6$  in  
16 sequence, the six points corresponding to coordinates on the X and Y axes and being  
17  $P_1(x,y)=(x'/4,0)$ ,  $P_2(x,y)=(3x'/4,0)$ ,  $P_3(x,y)=(3x'/4,y'/2)$ ,  $P_4(x,y)=(3x'/4,y')$ ,  $P_5(x,y)=(x'/4,y')$ ,  
18  $P_6(x,y)=(x'/4,y'/2)$ , the six lines including at least two straight lines and up to four curved  
19 lines.

1 8. (Currently Amended) [[The]] An apparatus of claim 6, comprising:

2 a tension mask having a screen part for transmitting electron beams, the screen part  
3 having a first area including a center region of the screen part, and having a second area  
4 distinguishable from the first area and not including the center region of the screen part; and  
5 a mask frame coupled to said tension mask for reinforcing structural strength of said  
6 tension mask while applying tension to said tension mask;

7 the screen part including a plurality of real slots, dummy slots and strip parts, the real  
8 slots being located in the first area, the dummy slots being located in the second area;

9           the screen part having a first edge region substantially parallel to an X axis, the first  
10 area being symmetrically formed around a first imaginary line parallel to the X axis, the first  
11 area being symmetrically formed around a second imaginary line perpendicular to the X axis;

12           the screen part having the first edge region on the X axis and a second edge region on  
13 a Y axis perpendicular to the X axis, the X and Y axes crossing each other at a corner region  
14 of the screen part, the first edge region having a length  $x'$  and the second edge region having  
15 a length  $y'$ , the first area being bordered by six lines connecting six points  $P_1$  to  $P_6$  in  
16 sequence, the six points corresponding to coordinates on the X and Y axes and being  
17  $P_1(x,y)=(x'/4,0)$ ,  $P_2(x,y)=(3x'/4,0)$ ,  $P_3(x,y)=(2x'/3,y'/2)$ ,  $P_4(x,y)=(3x'/4,y')$ ,  $P_5(x,y)=(x'/4,y')$ ,  
18  $P_6(x,y)=(x'/3,y'/2)$ , the six lines including at least two straight lines and up to four curved  
19 lines.

1           9. (Currently Amended) [[The]] An apparatus of claim 6, comprising:

2           a tension mask having a screen part for transmitting electron beams, the screen part  
3 having a first area including a center region of the screen part, and having a second area  
4 distinguishable from the first area and not including the center region of the screen part; and  
5           a mask frame coupled to said tension mask for reinforcing structural strength of said  
6 tension mask while applying tension to said tension mask;

7           the screen part including a plurality of real slots, dummy slots and strip parts, the real  
8 slots being located in the first area, the dummy slots being located in the second area;

9           the screen part having a first edge region substantially parallel to an X axis, the first

10 area being symmetrically formed around a first imaginary line parallel to the X axis, the first  
11 area being symmetrically formed around a second imaginary line perpendicular to the X axis;

12 the screen part having the first edge region on the X axis and a second edge region on  
13 a Y axis perpendicular to the X axis, the X and Y axes crossing each other at a corner region  
14 of the screen part, the first edge region having a length  $x'$  and the second edge region having  
15 a length  $y'$ , the first area being bordered by six lines connecting six points  $P_1$  to  $P_6$  in  
16 sequence, the six points corresponding to coordinates on the X and Y axes and being  
17  $P_1(x,y)=(x'/3,0)$ ,  $P_2(x,y)=(2x'/3,0)$ ,  $P_3(x,y)=(3x'/4,y'/2)$ ,  $P_4(x,y)=(2x'/3,y')$ ,  $P_5(x,y)=(x'/3,y')$ ,  
18  $P_6(x,y)=(x'/4,y'/2)$ , the six lines including at least two straight lines and up to four curved  
19 lines.

1 10. (Currently Amended) [[The]] An apparatus of claim 6, comprising:

2 a tension mask having a screen part for transmitting electron beams, the screen part  
3 having a first area including a center region of the screen part, and having a second area  
4 distinguishable from the first area and not including the center region of the screen part; and  
5 a mask frame coupled to said tension mask for reinforcing structural strength of said  
6 tension mask while applying tension to said tension mask;

7 the screen part including a plurality of real slots, dummy slots and strip parts, the real  
8 slots being located in the first area, the dummy slots being located in the second area;

9 the screen part having a first edge region substantially parallel to an X axis, the first  
10 area being symmetrically formed around a first imaginary line parallel to the X axis, the first

11 area being symmetrically formed around a second imaginary line perpendicular to the X axis;

12 the screen part having the first edge region on the X axis and a second edge region on  
13 a Y axis perpendicular to the X axis, the X and Y axes crossing each other at a corner region  
14 of the screen part, the first edge region having a length  $x'$  and the second edge region having  
15 a length  $y'$ , the first area being bordered by lines connecting six points  $P_1$  to  $P_6$  in sequence,  
16 each of the six points  $P_1$  to  $P_6$  being located within a respective range, the locations of the six  
17 points corresponding to coordinates on the X and Y axes and being  $P_1(x,y)=(x'/4 \text{ to } x'/3,0)$ ,  
18  $P_2(x,y)=(2x'/3 \text{ to } 3x'/4,0)$ ,  $P_3(x,y)=(2x'/3 \text{ to } 3x'/4,y'/2)$ ,  $P_4(x,y)=(2x'/3 \text{ to } 3x'/4,y')$ ,  
19  $P_5(x,y)=(x'/4 \text{ to } x'/3,y')$ ,  $P_6(x,y)=(x'/4 \text{ to } x'/3,y'/2)$ .

Claim 11. (Canceled)

1 12. (Currently Amended) [[The]] An apparatus of claim 6, comprising:

2 a tension mask having a screen part for transmitting electron beams, the screen part  
3 having a first area including a center region of the screen part, and having a second area  
4 distinguishable from the first area and not including the center region of the screen part; and  
5 a mask frame coupled to said tension mask for reinforcing structural strength of said  
6 tension mask while applying tension to said tension mask;

7 the screen part including a plurality of real slots, dummy slots and strip parts, the real  
8 slots being located in the first area, the dummy slots being located in the second area;

9 the screen part having a first edge region substantially parallel to an X axis, the first

10 area being symmetrically formed around a first imaginary line parallel to the X axis, the first  
11 area being symmetrically formed around a second imaginary line perpendicular to the X axis;  
12 the first area being convexly shaped in a middle region of the second imaginary line.

1 13. (Currently Amended) A mask assembly for a cathode ray tube comprising:  
2 a tension mask having a screen part for transmitting electron beams, the screen part  
3 having a first area including a center region of the screen part, and having a second area  
4 distinguishable from the first area and not including the center region of the screen part; and  
5 a mask frame coupled to said tension mask for reinforcing structural strength of said  
6 tension mask while applying tension to said tension mask;  
7 the screen part including a plurality of real slots, dummy slots and strip parts, the real  
8 slots being located in the first area, the dummy slots being located in the second area;  
9 the first area including an upper part and a lower part, the upper part being spaced  
10 apart from the lower part, a center point at the center of the screen part being located between  
11 the upper and lower parts;  
12 the screen part having a first edge region substantially parallel to an X axis, the first  
13 area being symmetrically formed around a first imaginary line parallel to the X axis, the first  
14 area being symmetrically formed around a second imaginary line perpendicular to the X axis;  
15 the screen part having the first edge region on the X axis and a second edge region on  
16 a Y axis perpendicular to the X axis, the X and Y axes crossing each other at a corner region  
17 of the screen part, the first edge region having a length x' and the second edge region having

18 a length  $y'$ , the lower part being bordered by three lines connecting three points  $P_1$  to  $P_3$  in  
19 sequence, the upper part being bordered by three lines connecting three points  $P_4$  to  $P_6$  in  
20 sequence, the six points  $P_1$  to  $P_6$  corresponding to coordinates on the X and Y axes and being  
21  $P_1(x,y)=(x'/4,0)$ ,  $P_2(x,y)=(x'/2,y'/4)$ ,  $P_3(x,y)=(3x'/4,0)$ ,  $P_4(x,y)=(x'/4,y')$ ,  $P_5(x,y)=(x'/2,3y'/4)$ ,  
22  $P_6(x,y)=(3x'/4,y')$ .

1 14. (Original) The assembly of claim 13, the real slots in the first area being formed  
2 by a plurality of real bridges in the first area, each real bridge connecting adjacent ones of  
3 the strip parts to each other, the dummy slots in the second area being formed by a plurality  
4 of dummy bridges in the second area.

Claims 15-16. (Canceled)

1 17. (Currently Amended) A mask assembly for a cathode ray tube, comprising:  
2 a pair of supporting members;  
3 a pair of elastic members, each elastic member being disposed between and connected  
4 to said supporting members; and  
5 a mask coupled to said supporting members and being tensioned by said elastic  
6 members, said mask having a valid screen part forming a plurality of beam-passing apertures,  
7 the screen part having a first area including a center region of the screen part, and having a  
8 second area distinguishable from the first area and not including the center region of the



9 screen part;

10 the screen part including a plurality of real slots, dummy slots and strip parts, the real  
11 slots being located only in the first area, the dummy slots being located only in the second  
12 area;

13 the screen part having a first edge region substantially parallel to an X axis, the first  
14 area being symmetrically formed around a first imaginary line parallel to the X axis, the first  
15 area being symmetrically formed around a second imaginary line perpendicular to the X axis;  
16 the first area being concavely shaped in a middle region of the second imaginary line.

1 18. (Original) The assembly of claim 17, the first area being formed in a rectangular  
2 shape.

Claim 19. (Canceled)

1 20. (Currently Amended) [[The]] A mask assembly of claim 17, for a cathode ray  
2 tube, comprising:

3 a pair of supporting members;

4 a pair of elastic members, each elastic member being disposed between and connected  
5 to said supporting members; and

6 a mask coupled to said supporting members and being tensioned by said elastic  
7 members, said mask having a valid screen part forming a plurality of beam-passing apertures.

8 the screen part having a first area including a center region of the screen part, and having a  
9 second area distinguishable from the first area and not including the center region of the  
10 screen part;

11 the screen part including a plurality of real slots, dummy slots and strip parts, the real  
12 slots being located only in the first area, the dummy slots being located only in the second  
13 area;

14 the screen part having a first edge region substantially parallel to an X axis, the first  
15 area being symmetrically formed around a first imaginary line parallel to the X axis, the first  
16 area being symmetrically formed around a second imaginary line perpendicular to the X axis;

17 the first area being convexly shaped in a middle region of the second imaginary line.

1 21. (New) The assembly of claim 20, the first area being formed in a rectangular  
2 shape.

1 22. (New) The apparatus of claim 12, the real slots in the first area being formed by  
2 a plurality of real bridges in the first area, each real bridge connecting adjacent ones of the  
3 strip parts to each other, the dummy slots in the second area being formed by a plurality of  
4 dummy bridges in the second area.

1 23. (New) The apparatus of claim 22, the first area being symmetrically formed  
2 around a first axis and being symmetrically formed around a second axis perpendicular to the

3 first axis.

1 24. (New) The apparatus of claim 23, the first and second axes passing through a  
2 center point at a center of the screen part.

1 25. (New) The apparatus of claim 22, the first and second imaginary lines being  
2 straight lines passing through a center point at a center of the screen part.